

CLASS 1

Building Product Information Sheet

Product name (include the brand name):

DONN EXPOSED GRID CEILING SYSTEM - 5311RT

Product description and its intended use:

The Rondo DONN® Exposed Ceiling System provides the framework for a variety of lay-in tiles including: acoustic, perforated plasterboard, PVC laminated, and metal.

Suitable for:

Seismic design
Acoustic design

Compatible with Rondo Xpress® and KEY-LOCK®

Product identifier (if applicable):

(This could be a Global Trade Item Number (GTIN) or quick response code (QR code), or any other distinguishable part/model number or identifier.)

Place of manufacture: Aotearoa New Zealand Overseas

Legal and trading name of the manufacturer(s):

Rondo Building Services Pty Ltd

Address for service:

STREET NAME Building C1, 373 Neilson Street

SUBURB Penrose

CITY, COUNTRY Auckland, New Zealand

POSTCODE 1061

Website:

www.rondo.co.nz

Email address:

rondo@rondo.com.au

Phone no. (if applicable):

64 9 636 5110

NZBN (if applicable):

Selected system components manufactured overseas by:

Name: USG INTERNATIONAL, LTD.
Address: 3001 N.W. 125TH STREET, MIAMI, FLORIDA 33167
Website: www.usg.com



Legal and trading name of the importer (if applicable):

Rondo Building Services Pty Ltd

Address for service:

STREET NAME **Building C1, 373 Neilson Street** SUBURB **Penrose**

CITY, COUNTRY **Auckland, New Zealand** POSTCODE **1061**

Website:

www.rondo.co.nz

Email address:

Rondo.NewZealand@rondo.co.nz

Phone no. (if applicable):

64 9 636 5110

NZBN (if applicable):

Relevant Building Code clauses:

B1 Structure: Performance clauses B1.3.1, B1.3.2, B1.3.3 (a), (b), (c), (f), (l), (m) and B1.3.4 (a), (b), (d)
B2 Durability: Performance clauses B2.3.1 (b) (i), (ii), and B2.3.2

Statement on how the building product is expected to contribute to compliance:

Ceiling grid members and connections are designed in accordance with AS/NZS 4600:2018 Cold-formed steel structures to resist the vertical and horizontal design actions assessed for the relevant load combinations nominated in AS/NZS 1170.0:2002 Structural Design Actions – Part 0: General Principles.

Minimum requirements for the design comply with AS/NZS 2785:2020 Suspended Ceilings – Design and Installation. Rondo provides a 15-year structural system warranty which complies to Clause B2-Durability for non-structural building elements that are moderately difficult to access and replace.

- options for compliance set out in section 19 of the Act (regulations, acceptable solution, verification method)
- standard or technical document that describes the performance of the building product or the relevant specifications to which the building product was manufactured
- physical properties of the building product
- how the building product is intended to be used.

Limitations on the use of the building product:

It should be noted that Rondo products do not satisfy code requirements on their own, but deliver code compliant performance when used as part of full ceiling system, installed in accordance with specific Rondo technical literature.

Rondo Donn Exposed Grid Ceiling Systems are intended for internal, non-trafficable, non-fire rated applications only. Not suitable for indoor pool environments.

Design requirements that would support the appropriate use of the building product:

Rondo recommends that you seek professional advice relating to your unique architectural and building requirements, and that of the building code, to ensure the design is compliant.

We recommend that you contact Rondo NZ to obtain a design that is specifically customised to your project requirements. This service is complementary.

Installation requirements:

Rondo recommends that this system is installed by a qualified trades person and in accordance with the relevant codes and standards. Refer to Rondo literature (www.rondo.co.nz), in conjunction with any design requirements.

Maintenance requirements *(also provide link to the product maintenance guide)*:

Cleaning - Remove ceiling panels, then perform necessary cleaning of the grid with non-solvent based proprietary cleaner.

Painting - Repainting of grid system members should be with a high-quality solvent-based paint for use over metal surfaces and applied as recommended by the paint manufacturer.

Paint Colour -

Powder coating: PPG Industries - Product Code PE522 polyester matt Colour Code 9249AN ANOGRain Pacific White Wet spray: PPG Industries - Product Code 262 Speedlac (nitro-cellulose laquer) Colour Code 34063 Pacific White NZ Titan Coatings 319-4114 Flat Black (0205) 311-3430 Flat White (AKA Pacific White locally) (0050)

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?:

Yes No

If yes, description of the warning or ban under section 26:

N/A

Date: 01/12/2023